



SilentDrive Elite myQ

Your Home, On Command



OR



DOOR TYPES: residential rolling garage doors **DOOR SIZE:** up to 18m²

Key Benefits



Compliant to Australian and New Zealand Standard AS/NZS 60335-2-95



Security+2.0

Transmitters communicate on multiple frequencies with encrypted rolling code. This ensures the strongest frequency is selected every time, virtually eliminating interference while providing the highest level of security.



MyQ Technology

Monitor, control and receive alert notifications on your SilentDrive Elite MyQ away from home. Through the use of either your Smart phone, Tablet or Computer you can monitor and control the garage door remotely. Anytime scheduling to close your garage door. Your Home, On Command.



Up to 75% less energy*

Advanced technology uses less than 1 watt of power whilst in standby mode, meeting the world's toughest energy standards.



Quiet and Powerful Motor

The powerful and fast DC motor is quiet and built to last with the strength to open any branded domestic door.



Improved Transmitter Range

Tested against other products, these transmitters have up to 18% better range which means you can start opening your garage door sooner.



Soft Start / Stop Function

Designed to ensure smooth and quiet door operation.



7 Year Warranty

Backed by a 7 year / 15,000 cycle warranty** we stand behind our products with an after sales support team that we believe are the best in the industry.

Standard Merlin Safety Features



Premium Automatic Safety Reverse

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop going up.



Automatic Force Sensing

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door.



Manual Release

In case of power failure you can simply activate the manual release to open your garage door.

*when compared to other available products **conditions apply



Kit Contents

1 x Powerhead



2 x Premium+ remote controls E960M



Two channel wireless wall button E138M




Protector system safety beam sensors 774ANZ



MyQ Gateway 828AU

SPECIFICATIONS


- 24V DC motor with thermal overload protection
- Input voltage: 240V AC
- Rated door area up to 18m²
- Drum rotations: 4.5
- Max door weight: up to 120kg
- Max peak pulling force: 550 N
- Minimum side room 45mm
- 433.30, 434.54, 433.92 MHz AM radio with Security+2.0 encrypted rolling code technology.
- Up to 64 memory registers
- Garage illumination: 12 premium ultrabright LEDs
- Noise rating 1M : 59DB
- MyQ Technology




DOOR SPECIFICATIONS

- Maximum lifting under spring tension = 20kg
- Suitable for steel spring balanced doors

DOOR OPENING AND CLOSING TIMES





13 seconds



13 seconds
(based on a 2.3m high door)

Door height: 4.5m, 3.0m Door width: 4.0m, 6.0m
Single dwelling, max door weight: up to 120kg

TYPICAL INSTALLATION



OPTIONAL ACCESSORIES



Four channel
key ring
mini-transmitters
E950M



Wall or visor
mounted three
channel transmitter
E943M



Wall or visor
mounted single
channel transmitter
E940M



3 channel mini
transmitter
E945M



Wireless keypad
E840M

CHAMBERLAIN[®]

The World's Largest Manufacturer of Garage Door Openers

Australia Phone: 1800 638 234 Fax: 1800 888 121 Web: gomerlin.com.au

New Zealand Phone: 0800 653 667 Fax: 0800 653 663 Web: gomerlin.co.nz

™ Trademark of The Chamberlain Group, Inc. ® Registered Trademark of the Chamberlain Group, Inc.
© 2017 The Chamberlain Group, Inc.